

# PRODUCT DATA SHEET



MFR 0.3  
Density 921 **ETILINAS PETLIN LDPE N103X**

## Low Density Polyethylene

### DESCRIPTION

**ETILINAS PETLIN LDPE N103X** is a low density polyethylene resin for heavy duty film applications. It is produced by the state-of-the-art DSM Stamicarbon tubular process. It contains antioxidant (BHT free) additives. It is intended primarily for blown film process. This product meets the United State Food and Drug Administration (US FDA) criteria for food contact use and Commission Regulation (EU).

### CHARACTERISTICS include:

- Low gels
- Outstanding shrink properties
- High strengths
- Very low energy consumptions during processing

### APPLICATIONS include:

Heavy duty films : shrink films, sacks, industrial liners, construction films, pond liners, greenhouse films, surface protection films.

### RECOMMENDED GAUGES:

45 - 280 microns

### TYPICAL DATA:

45 microns film

Product Properties*	Test Method	Units	Value
<b>General Properties</b>			
Melt Flow Rate, I <sub>2</sub>	ASTM D 1238;B @ 190°C, 2.16kg	g/10min	0.3
Nominal Density	ASTM D 792	kg/m <sup>3</sup>	921
Melting Temperature	ASTM D 3417	°C	111
Vicat Softening Temperature	ASTM D 1525 (Load: 1 kg; Heating rate: 50°C/hr)	°C	94
<b>Mechanical Properties</b>			
Tensile Strength at Break, (MD/TD)	ASTM D 882	MPa	30/27
Elongation at Break, (MD/TD)	ASTM D 882	%	169/545
Elmendorf Tear Strength, (MD/TD)	ASTM D 1922	g/25µm	216/194
Dart Impact Strength	ASTM D 1709-15a	g	266
<b>Other Properties</b>			
Clarity	ASTM D 1746	%	90
Gloss (45°)	ASTM D 2457	GU	43
Haze	ASTM D 1003	%	14
Coefficient of Friction (COF)	ASTM D 1894	-	0.7

\*The physical properties shown are typical values obtained by averaging a number of test results and small divergence from quoted figures may occur.

## Typical Processing Conditions

Extrusion melt temperature of **ETILINAS PETLIN LDPE N103X** in the range of from 170°C~190°C depending on the type of machine. For blown film, recommended blow-up ratio of 1.5 to 3.5 : 1.

# PRODUCT DATA SHEET



MFR 0.3  
Density 921

## ETILINAS PETLIN LDPE N103X

### Low Density Polyethylene

#### REGULATORY

ETILINAS PETLIN LDPE N103X complies with the following specification when processed using good extrusion practice:-

- USFDA Regulation 21 CFR 177.1520 and CFR 178.2010
- Commission Regulation (EU) No. 10/2011
- Complies to heavy metal and phthalate content in accordance to Directive 2011/65/EU (RoHS)
- Does not contain any of the Substances of Very High Concern (SVHC) as identified under Article 33 of Regulation (EC) No 1907/2006 (REACH)
- HALAL certified, JAKIM/(S)/(22.00)/492/2/1 044-03/2011

#### AVAILABILITY

ETILINAS PETLIN LDPE N103X are available 25kg bags. The product type and batch number are clearly marked on each bag.

#### STORAGE/HANDLING

ETILINAS PETLIN LDPE N103X should be properly stored in well ventilated environment at a temperature of below 50°C. Prolonged or improper storage can result in deterioration of product properties. The PETRONAS Chemicals Safety Data Sheet (SDS) contains important safety information and should be viewed before using the product.

#### HEALTH & SAFETY

ETILINAS PETLIN LDPE N103X is not classified as a dangerous preparation. Please refer to our Safety Data Sheet (SDS) for details on various aspects of safety, recovery and disposal of the product.

#### PRODUCT STEWARDSHIP

PETRONAS aims to increase awareness of all the hazards associated with the storage, handling and use of its products. Thoroughly reviewing the accompanying Safety Data Sheets and disseminating the information to all dependent and interested parties is an essential part of any 'Responsible Care' programme.

#### RELATED DOCUMENTS

The following related documents are available on request, and represent various aspects on the usability, safety, recovery and disposal of the product.

- Safety Data Sheet (SDS)
- Statement on chemicals, regulations and standards
- Statement on compliance to food contact regulations

#### FOR MORE INFORMATION

Please contact **PETRONAS Chemicals Group Berhad (PCG)**, Tower 1, PETRONAS Twin Towers, Kuala Lumpur City Centre, 50088 Kuala Lumpur, Malaysia.

For product queries, kindly email us at [polymer.pcg@petronas.com](mailto:polymer.pcg@petronas.com)



#### IMPORTANT NOTICE

Information contained in this document is accurate and reliable to the best of the knowledge and belief of PETRONAS Chemicals Group Berhad the suggestions and recommendations offered herein serve as a guide in the use of these material, and cannot be guaranteed because the conditions of use are beyond PCG's control. PCG assumes no responsibility for the use of information supplied, the application, adaption or processing of the products described herein and here by disclaims all liability (except as otherwise provided by the law) in regard to such use.